

Printing date: 22.01.2024 Version number: 2.0 (replaces version 1.0) Revision: 22.01.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking:

1.1 Product identifier:

Trade name: Binding buffer LU UFI: NTJ9-WMUM-Q00A-X7UM

1.2 Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

Application of the substance / the preparation: Laboratory chemicals

1.3 Details of the supplier of the safety data sheet:

Manufacturer/Supplier:

LGC Genomics GmbH

Ostendstr. 25

12459 Berlin • Germany Tel. +49 (0)30 5304 2200

Fax. +49 (0)30 5304 2201

Email: techsupport@LGCGroup.com

Further information obtainable from: Business Unit Nucleic Acid Preparation

1.4 Emergency telephone number:

Giftinformationszentrum Mainz / Poison Information Center Mainz, Germany

Tel.: +49-(0)-6131-19240 / 24 h

SECTION 2: Hazards identification:

2.1 Classification of the substance or mixture:

Classification according to Regulation (EC) No 1272/2008:



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements:

Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

Hazard pictograms:







GHS02 GHS05 GHS07

Signal word: Danger





Printing date: 22.01.2024 Version number: 2.0 (replaces version 1.0) Revision: 22.01.2024

Trade name: Binding buffer LU

(Contd. of page 1)

Hazard-determining components of labelling:

alcohols, C12-14-secondary, ethoxylated

propan-2-ol acetic acid

Hazard statements:

H225 Highly flammable liquid and vapour. H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards:

Results of PBT and vPvB assessment:

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients:

3.2 Mixtures:

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

EINECS: 200-661-7

CAS: 67-63-0 propan-2-ol

♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336

CAS: 84133-50-6 alcohols, C12-14-secondary, ethoxylated >25-≤50%

EC number: 617-534-0 Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin

Irrit. 2, H315

CAS: 64-19-7 acetic acid ≤2.5%

Specific concentration limits: Skin Corr. 1A; H314: C ≥ 90 %

Skin Corr. 1B; H314: $25 \% \le C < 90 \%$ Skin Irrit. 2; H315: $10 \% \le C < 25 \%$ Eye Irrit. 2; H319: $10 \% \le C < 25 \%$

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures:

4.1 Description of first aid measures:

General information:

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

After inhalation: Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)

>25-<50%





Printing date: 22.01.2024 Version number: 2.0 (replaces version 1.0) Revision: 22.01.2024

Trade name: Binding buffer LU

(Contd. of page 2)

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed:

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

SECTION 5: Firefighting measures:

5.1 Extinguishing media:

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture: Can form explosive gas-air mixtures.

5.3 Advice for firefighters:

Protective equipment:

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures:

6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities:

Storage:

Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Further information about storage conditions: Keep container tightly sealed.

Storage class: 3

7.3 Specific end use(s): No further relevant information available.

(Contd. on page 4)





Printing date: 22.01.2024 Version number: 2.0 (replaces version 1.0) Revision: 22.01.2024

Trade name: Binding buffer LU

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection:

8.1 Control parameters:

Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

OEL Short-term value: 400 ppm Long-term value: 200 ppm

Sk

64-19-7 acetic acid

OEL Short-term value: 50 mg/m³, 20 ppm Long-term value: 25 mg/m³, 10 ppm

IOELV

8.2 Exposure controls:

Appropriate engineering controls: No further data; see section 7.

Individual protection measures, such as personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection: Use suitable respiratory protective device in case of insufficient ventilation.

Hand protection: Protective gloves

Material of gloves: Nitrile rubber, NBR

Nitrile rupper, NBR

Recommended thickness of the material: ≥ 0.35 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection: Tightly sealed goggles

SECTION 9: Physical and chemical properties:

9.1 Information on basic physical and chemical properties:

General Information:

Physical state: Fluid
Colour: Colourless
Odour: Characteristic
Odour threshold: Not determined.
Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range: 81.1 °C **Flammability:** Not applicable.

Lower and upper explosion limit:

 Lower:
 2 Vol % (67-63-0 propan-2-ol)

 Upper:
 12 Vol % (67-63-0 propan-2-ol)

Flash point: 21 °C Auto-ignition temperature: 360 °C

Decomposition temperature: Not determined.

pH at 20 °C: 4.5

(Contd. on page 5)





Printing date: 22.01.2024 Version number: 2.0 (replaces version 1.0) Revision: 22.01.2024

Trade name: Binding buffer LU

(Contd. of page 4)

Viscosity:

Kinematic viscosity: Dynamic:Not determined.
Not determined.

Solubility:

water: Fully miscible.

Partition coefficient n-octanol/water (log value): Not determined.

Vapour pressure at 20 °C: 19 hPa

Density and/or relative density:

Density at 20 °C: 0.896 g/cm³
Relative density: Not determined.
Vapour density: Not determined.

9.2 Other information:

Appearance:

Form: Fluid

Important information on protection of health

and environment, and on safety.:

Ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Change in condition:

Evaporation rate: Not determined.

Information with regard to physical hazard

classes:

Explosives: Void
Flammable gases: Void
Aerosols: Void
Oxidising gases: Void
Gases under pressure: Void

Flammable liquids: Highly flammable liquid and vapour.

Flammable solids: Void **Self-reactive substances and mixtures:** Void Pyrophoric liquids: Void **Pyrophoric solids:** Void Self-heating substances and mixtures: Void Substances and mixtures, which emit flammable gases in contact with water: Void Oxidising liquids: Void Oxidising solids: Void Organic peroxides: Void Corrosive to metals: Void **Desensitised explosives:** Void

SECTION 10: Stability and reactivity:

10.1 Reactivity: No further relevant information available.

10.2 Chemical stability:

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions:

Reacts with oxidising agents.

Forms explosive gas mixture with air.

10.4 Conditions to avoid: No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)





Printing date: 22.01.2024 Version number: 2.0 (replaces version 1.0) Revision: 22.01.2024

Trade name: Binding buffer LU

(Contd. of page 5)

10.6 Hazardous decomposition products:

Flammable gases/vapours

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information:

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

Acute toxicity:

Harmful if swallowed or if inhaled.

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 >1,468 mg/kg (rat)

Inhalative LC50/4 h 5.34 mg/l

67-63-0 propan-2-ol

Oral LD50 5,840 mg/kg (rat) (OECD 401)

Dermal LD50 13,800 mg/kg (rabbit) (OECD 402)

Inhalative LC50/4 h >25 mg/l /6 h (rat) (OECD 403)

84133-50-6 alcohols, C12-14-secondary, ethoxylated

Oral LD50 >412 mg/kg (rat)

Dermal LD50 >14,000 mg/kg (rat)

Inhalative LC50/4 h 1.5 mg/l (ATE)

64-19-7 acetic acid

Oral LD50 3,310 mg/kg (rat)
Dermal LD50 1,060 mg/kg (rabbit)

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Causes serious eye damage.

Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards: Endocrine disrupting properties:

None of the ingredients is listed.

SECTION 12: Ecological information:

12.1 Toxicity:

Aquatic toxicity:

67-63-0 propan-2-ol

EC50 >100 mg/l (algae)

LC50 9,714 mg/l /24 h (daphnia) (OECD 202)

9,640 mg/l /96 h (fish) (OECD 203)

84133-50-6 alcohols, C12-14-secondary, ethoxylated

EC50 7.3 mg/l /48 h (daphnia)

(Contd. on page 7)





Printing date: 22.01.2024 Version number: 2.0 (replaces version 1.0) Revision: 22.01.2024

Trade name: Binding buffer LU

(Contd. of page 6)

LC50 3.2 mg/l /96 h (fish)

12.2 Persistence and degradability: No further relevant information available. **12.3 Bioaccumulative potential:** No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

12.5 Results of PBT and vPvB assessment:

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties:

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects:

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations:

13.1 Waste treatment methods:

European waste catalogue:

Dispose of contents/container in accordance with local/regional/national/international regulations.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information:

14.1 UN number or ID number:

ADR, IMDG, IATA UN1219

14.2 UN proper shipping name:

ADR 1219 ISOPROPANOL (ISOPROPYL ALCOHOL)
IMDG, IATA ISOPROPANOL (ISOPROPYL ALCOHOL)

Ш

14.3 Transport hazard class(es):

ADR, IMDG, IATA



Class: 3 Flammable liquids.

Label: 3

14.4 Packing group: ADR, IMDG, IATA

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user: Warning: Flammable liquids.

Hazard identification number (Kemler code): 33

EMS Number: F-E,S-D

Stowage Category: B

14.7 Maritime transport in bulk according to IMO

instruments: Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ):

(Contd. on page 8)





Version number: 2.0 (replaces version 1.0) Revision: 22.01.2024 Printing date: 22.01.2024

Trade name: Binding buffer LU

(Contd. of page 7)

Transport category: 2 **Tunnel restriction code:** D/E

UN "Model Regulation": UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL),

SECTION 15: Regulatory information:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Directive 2012/18/EU:

Named dangerous substances - ANNEX I: None of the ingredients is listed.

Seveso category: P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements: 5,000 t Qualifying quantity (tonnes) for the application of upper-tier requirements: 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII: Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical

and electronic equipment - Annex II:

None of the ingredients is listed. **REGULATION (EU) 2019/1148:**

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3)):

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS:

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors:

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors:

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

Department issuing SDS:

ADEEGO GmbH Wildsteig 4A

D-42113 Wuppertal

Tel. +49 (0) 202 2575700 Fax. +49 (0) 202 2575701

Email: mail@adeego.de

www.adeego.de

(Contd. on page 9)





Printing date: 22.01.2024 Version number: 2.0 (replaces version 1.0) Revision: 22.01.2024

Trade name: Binding buffer LU

(Contd. of page 8)

© Copyright by ADEEGO GmbH

Contact: Dr. Axel Deeg

Version number of previous version: 1.0

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3